

OKS 2661 - Product Information

Fields of Application:

Degreasing of all sliding surfaces and parts of non-absorbent materials, e.g. metals, ceramic or many plastics and elastomers. Before use of OKS lubricants, cleaning of all surfaces for coatings, paints or adhesives and sealants, all friction surfaces on which high friction forces are transmitted, e.g. clutch and brake linings. Removal of aged and gummy oil and grease residues, of undesirable residues of brake fluids and silicones, of residues of simple coatings, adhesives and sealants.

Advantages and Benefits:

Highly effective due to a workplace and environment-friendly, complex formulation of several actively cleaning substances. Excellently suited for cleaning all surfaces in industry, trade, workshop, hobby and household. Modern active cleaner on a solvent base. Fast 100% evaporation of the cleaner.

Application:

Spray generous quantities onto the surfaces from a short distance so that even the mechanical cleaning effect of the spray is used. Cleaning is made even more effective if you simultaneously rub away at the surface with paper or cellulose cloths. Next, allow to dry completely (about 1 minute at room temperature). Dab away running cleaner with absorbent material and allow to evaporate in open air. Use only in well-ventilated rooms or in the open air. Some types of plastic or rubber (for example, thermoplastics such as PVC, plexiglass, polystyrene and similar) and paints could be attacked. We recommend therefore that you check the resistance before use. Our customer advice service will be pleased to help should you have any further questions.


Additional Information:

Packaging (Article number): - 600 ml Spray (02611006)

Version: E-10.1/05

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitratily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimburesement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. (B) = Registered Trademark

OKS 2661 Fast Cleaner, Spray





Technical Data

	Norm	Conditions	Unit	Value
Base Oil				
Туре				Blend of solvents
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	0,725
Colour				colourless

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitratily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimburesement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. (**)